

**Ongoing Face Recognition
Vendor Test (FRVT)**
Part 1: Verification

Patrick Grother
Mei Ngan
Kayee Hanaoka
*Information Access Division
Information Technology Laboratory*

This publication is available free of charge from:
<https://www.nist.gov/programs-projects/face-recognition-vendor-test-frvt-ongoing>

DISCLAIMER

Specific hardware and software products identified in this report were used in order to perform the evaluations described in this document. In no case does identification of any commercial product, trade name, or vendor, imply recommendation or endorsement by the National Institute of Standards and Technology, nor does it imply that the products and equipment identified are necessarily the best available for the purpose.

ABOUT THIS REPORT

This report documents the verification-track of the ongoing Face Recognition Vendor Test. The report will be updated continuously as new algorithms are evaluated, as new datasets are added, and as new analyses are included. Comments and suggestions should be directed to frvt@nist.gov.

Contents

DISCLAIMER	1
1 ALGORITHM SUMMARIES	4
2 DATASETS	5
2.1 VISA IMAGES	5
2.2 MUGSHOT IMAGES	5
3 RESULTS	5
3.1 OVERALL ACCURACY	5
3.2 GENUINE DISTRIBUTION STABILITY	12
3.2.1 EFFECT OF BIRTH PLACE ON THE GENUINE DISTRIBUTION	12
3.2.2 EFFECT OF AGE ON GENUINE SUBJECTS	14
3.3 IMPOSTOR DISTRIBUTION STABILITY	16
3.3.1 EFFECT OF BIRTH PLACE ON THE IMPOSTOR DISTRIBUTION	16
3.3.2 EFFECT OF AGE ON IMPOSTORS	34

List of Tables

1 ALGORITHM SUMMARY, TEMPLATE SIZE, TEMPLATE TIME	4
---	---

List of Figures

1 DETECTION ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES	7
2 DETECTION ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES	8
3 FALSE MATCH RATE CALIBRATION: VISA IMAGES	9
4 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES	10
5 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES	11
6 EFFECT OF COUNTRY OF BIRTH ON FNMR	13
7 EFFECT OF SUBJECT AGE ON FNMR	15
8 ALGORITHM DERMALOG-001 CROSS REGION FMR	18
9 ALGORITHM DERMALOG-002 CROSS REGION FMR	19
10 ALGORITHM NTECHLAB-000 CROSS REGION FMR	20
11 ALGORITHM 3DIVI-000 CROSS REGION FMR	21
12 ALGORITHM RANKONE-000 CROSS REGION FMR	22
13 ALGORITHM NEUROTECHNOLOGY-000 CROSS REGION FMR	23
14 ALGORITHM VCOG-001 CROSS REGION FMR	24
15 ALGORITHM VIGILANTSOLUTIONS-000 CROSS REGION FMR	25
16 ALGORITHM DERMALOG-001 CROSS COUNTRY FMR	26
17 ALGORITHM DERMALOG-002 CROSS COUNTRY FMR	27
18 ALGORITHM NTECHLAB-000 CROSS COUNTRY FMR	28
19 ALGORITHM 3DIVI-000 CROSS COUNTRY FMR	29
20 ALGORITHM RANKONE-000 CROSS COUNTRY FMR	30
21 ALGORITHM NEUROTECHNOLOGY-000 CROSS COUNTRY FMR	31
22 ALGORITHM VCOG-001 CROSS COUNTRY FMR	32
23 IMPOSTOR COUNTS FOR CROSS COUNTRY FMR CALCULATIONS	33
24 ALGORITHM DERMALOG-001 CROSS AGE FMR	35
25 ALGORITHM DERMALOG-002 CROSS AGE FMR	36
26 ALGORITHM NTECHLAB-000 CROSS AGE FMR	37
27 ALGORITHM 3DIVI-000 CROSS AGE FMR	38
28 ALGORITHM RANKONE-000 CROSS AGE FMR	39

29	ALGORITHM NEUROTECHNOLOGY-000 CROSS AGE FMR	40
30	ALGORITHM VCOG-001 CROSS AGE FMR	41
31	ALGORITHM VIGILANTSOLUTIONS-000 CROSS AGE FMR	42

1 Algorithm summaries

Developer	Short	Seq. number	Validation date	Size config data (KB)	Template size (B)	Template time (ms)	GPU
3DiVi	3divi	000	2017-03-16	169360	511 ± 16	276 ± 58	Yes
Dermalog	dermalog	001	2017-02-22	0	1041 ± 47	107 ± 4	No
Dermalog	dermalog	002	2017-02-22	0	1041 ± 47	83 ± 7	No
Neurotechnology	neurotech	000	2017-03-22	62129	7148 ± 0	609 ± 47	No
N-Tech Lab	ntech	000	2017-03-13	191530	2906 ± 1	277 ± 12	No
Rank One Computing	rankone	000	2017-03-21	0	144 ± 0	83 ± 10	No
VCognition	vcog	001	2017-03-28	86103	4126	-	No
Vigilant Solutions	vigilant	000	2017-03-30	352218	31540 ± 0	851 ± 92	No

Table 1: The entries show the algorithms included in this report

2 Datasets

2.1 Visa images

- ▷ The number of images is $O(10^5)$
- ▷ The number of subjects is $O(10^5)$
- ▷ The number of subjects with two images $O(10^4)$
- ▷ The images have geometry in reasonable conformance with the ISO/IEC 19794-5 Full Frontal image type. Pose is generally excellent.
- ▷ The images are of size 252x300 pixels. The mean IOD is 69 pixels.
- ▷ The images are of subjects from greater than 100 countries, with significant imbalance due to visa issuance patterns.
- ▷ The images are of subjects of all ages, including children, again with imbalance due to visa issuance demand.
- ▷ Many of the images are live capture. A substantial number of the images are photographs of paper photographs.

2.2 Mugshot images

- ▷ The number of images is $O(10^6)$
- ▷ The number of subjects is $O(10^5)$
- ▷ The number of subjects with two images $O(10^5)$
- ▷ The images have geometry in reasonable conformance with the ISO/IEC 19794-5 Full Frontal image type.
- ▷ The images are of variable sizes. The median IOD is 104 pixels. The mean IOD is 123 pixels.
- ▷ The images are of subjects from the United States.
- ▷ The images are of subjects of adults.
- ▷ The images are all live capture.

3 Results

3.1 Overall accuracy

Goals:

- ▷ To state overall accuracy.
- ▷ To compare algorithms.

Method: For visa images:

- ▷ The comparisons are of visa photos against visa photos.
- ▷ The number of genuine comparisons is $O(10^4)$.
- ▷ The number of impostor comparisons is $O(10^{10})$.

- ▷ The comparisons are fully zero-effort, meaning impostors are paired without attention to sex, age or other covariates. However, later analysis is conducted on subsets.
- ▷ The number of persons is $O(10^5)$.
- ▷ The number of images used to make a template is 1.
- ▷ The number of templates used to make each comparison score is two corresponding to simple one-to-one verification.

For mugshot images:

- ▷ The comparisons are of mugshot photos against mugshot photos.
- ▷ The number of genuine comparisons is $O(10^5)$.
- ▷ The number of impostor comparisons is $O(10^7)$.
- ▷ The comparisons are fully zero-effort, meaning impostors are paired without attention to sex, age or other covariates.
- ▷ The number of persons is $O(10^6)$.
- ▷ The number of images used to make a template is 1.
- ▷ The number of templates used to make each comparison score is two corresponding to simple one-to-one verification.

Summary: Core algorithm accuracy is stated via the error tradeoff characteristics of Figures 1 and 2.

Figure 3 shows dependence of false match rate on algorithm score threshold. This allows a deployer to set a threshold to target a particular false match rate appropriate to the security objectives of the application.

Figure 4 likewise shows FMR(T) but for mugshots, and specially four subset of the population.

Note that in both the mugshot and visa sets false match rates vary with the ethnicity, age, and sex, of the enrollee and impostor - see section 3.3.




Figure 1: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate plotted parametrically on threshold, T . The scales are logarithmic in order to show many decades of FMR.




Figure 2: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T . The scales are logarithmic in order to show decades of FMR.




Figure 3: For the visa images, the false match calibration curves show false match rate vs. threshold.




Figure 4: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.




Figure 5: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The grey lines correspond to fixed thresholds, showing how both FNMR and FMR vary at one operating threshold. Important: Many of the plots will naively be read as saying whites gives lower error rates than blacks because the blue traces lie beneath the red ones. However, this is misleading and incomplete: The grey lines show the traces are generally shifted horizontally. Thus for the dermalog-001 algorithm FNMR for whites is higher than for blacks at a fixed threshold but, at the same time, FMR is higher for blacks - see Figure 4. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.

3.2 Genuine distribution stability

3.2.1 Effect of birth place on the genuine distribution

Background: Both skin tone and bone structure vary geographically. Prior studies have reported variations in FNMR and FMR.

Goal: To measure false non-match rate (FNMR) variation with country of birth.

Methods: Thresholds are determined that give $FMR = \{0.001, 0.0001\}$ over the entire impostor set. Then FNMR is measured over 1000 bootstrap replications of the genuine scores. Only those countries with at least 140 individuals are included in the analysis.

Results: Figure 6 shows FNMR by country of birth for the two thresholds.

Caveats: The results may not relate to subject-specific properties. Instead they could reflect image-specific quality differences, which could occur due to collection protocol or software processing variations.




Figure 6: The figures shows an order of magnitude variation in FNMR across country of birth.

3.2.2 Effect of age on genuine subjects

Background: Faces change appearance throughout life. Face recognition algorithms have previously been reported to give better accuracy on older individuals (See NIST IR 8009).

Goal: To quantify false non-match rates (FNMR) as a function of age. We do not aim to quantify ageing effects here as the separation between two samples is limited to just a few years.

Methods: Using the visa images, thresholds are determined that give FMR = 0.001 and 0.0001 over the entire impostor set. Then FNMR is measured over 1000 bootstrap replications of the genuine scores. Only those countries with at least 30 individuals are included in the analysis.

Results: For the visa images, Figure 7 shows how false non-match rates for genuine users, as a function of age group.

The notable aspects are:

- ▷ Younger subjects give considerably higher FNMR. This is likely due rapid growth and change in facial appearance.
- ▷ FNMR trends down throughout life. The last bin, AGE > 72, contains fewer than 140 mated pairs, and may be affected by small sample size.

Caveats: None.




Figure 7: For the visa images, the dots show FNMR by age group for three operating thresholds corresponding to FMR = {0.01, 0.001, 0.0001} computed over all $O(10^{10})$ impostor scores. Given a pair of face images taken at different times, we assign a false non-match to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands. However the FNMR for the first and last bins are each computed over fewer than 150 comparisons.

3.3 Impostor distribution stability

3.3.1 Effect of birth place on the impostor distribution

Background: Facial appearance varies geographically, both in terms of skin tone, cranio-facial structure and size. This section addresses whether false match rates vary intra- and inter-regionally.

Goals:

- ▷ To show the effect of birth region of the impostor and enrollee on false match rates.
- ▷ To determine whether some algorithms give better impostor distribution stability.

Methods:

- ▷ For the visa images, NIST defined 10 regions: Sub-Saharan Africa, South Asia, Polynesia, North Africa, Middle East, Europe, East Asia, Central and South America, Central Asia, and the Caribbean.
- ▷ For the visa images, NIST mapped each country of birth to a region. There is some arbitrariness to this. For example, Egypt could reasonably be assigned to the Middle East instead of North Africa. An alternative methodology could, for example, assign the Philippines to *both* Polynesia and East Asia.
- ▷ FMR is computed for cases where all face images of impostors born in region r_2 are compared with enrolled face images of persons born in region r_1 .

$$\text{FMR}(r_1, r_2, T) = \frac{\sum_{i=1}^{N_{r_1, r_2}} H(s_i - T)}{N_{r_1, r_2}} \quad (1)$$

where the same threshold, T , is used in all cells, and H is the unit step function. The threshold is set to give $\text{FMR}(T) = 0.001$ over the entire set of visa image impostor comparisons.

- ▷ This analysis is then repeated by country-pair, but only for those country pairs where both have at least 1000 images available. The countries¹ appear in the axes of graphs that follow.
- ▷ The mean number of impostor scores in any cross-region bin is 33 million. The smallest number of impostor scores in any bin is 135000, for Central Asia - North Africa. While these counts are large enough to support reasonable significance, the number of individual faces is much smaller, $O(N^{0.5})$.
- ▷ The numbers of impostor scores in any cross-country bin is shown in Figure 23.

Results: Subsequent figures show heatmaps that use color to represent the base-10 logarithm of the false match rate. Red colors indicate high (bad) false match rates. Dark colors indicate benign false match rates. There are two series of graphs corresponding to aggregated geographical regions, and to countries. The notable observations are:

- ▷ The on-diagonal elements correspond to within-region impostors. FMR is generally above the nominal value of $\text{FMR} = 0.001$. Particularly there is usually higher FMR in, Sub-Saharan Africa, South Asia, and the Caribbean. Europe and Central Asia, on the other hand, usually give FMR closer to the nominal value.
- ▷ The off-diagonal elements correspond to across-region impostors. The highest FMR is produced between the Caribbean and Sub-Saharan Africa.
- ▷ Algorithms vary.

¹These are Argentina, Australia, Brazil, Chile, China, Costa Rica, Cuba, Czech Republic, Dominican Republic, Ecuador, Egypt, El Salvador, Germany, Ghana, Great Britain, Greece, Guatemala, Haiti, Hong Kong, Honduras, Indonesia, India, Israel, Jamaica, Japan, Kenya, Korea, Lebanon, Mexico, Malaysia, Nepal, Nigeria, Peru, Philippines, Pakistan, Poland, Romania, Russia, South Africa, Saudi Arabia, Thailand, Trinidad, Turkey, Taiwan, Ukraine, Venezuela, and Vietnam.

- ▷ We computed the same quantities for a global FMR = 0.0001. The effects are similar.

Caveats:

- ▷ The effects of variable impostor rates on one-to-many identification systems may well differ from what's implied by these one-to-one verification results. Two reasons for this are a) the enrollment galleries are usually imbalanced across countries of birth, age and sex; b) one-to-many identification algorithms often implement techniques aimed at stabilizing the impostor distribution. Further research is necessary.
- ▷ In principle, the effects seen in this subsection could be due to differences in the image capture process. We consider this unlikely since the effects are maintained across geography - e.g. Caribbean vs. Africa, or Japan vs. China.

Cross region FMR at threshold T = 78.021 for algorithm dermalog_001, giving FMR(T) = 0.001 globally.




Figure 8: For algorithm dermalog-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.


Cross region FMR at threshold T = 78.171 for algorithm dermalog_002, giving $FMR(T) = 0.001$ globally.

Figure 9: For algorithm dermalog-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.

Cross region FMR at threshold T = 0.091 for algorithm ntechlab_000, giving FMR(T) = 0.001 globally.




Figure 10: For algorithm ntechlab-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.

Cross region FMR at threshold T = 2.869 for algorithm 3divi_000, giving FMR(T) = 0.001 globally.




Figure 11: For algorithm 3divi-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.


Cross region FMR at threshold T = 0.582 for algorithm rankone_000, giving $FMR(T) = 0.001$ globally.

Figure 12: For algorithm rankone-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.



Cross region FMR at threshold T = 30.260 for algorithm neurotechnology_000, giving $FMR(T) = 0.001$ globally.

Figure 13: For algorithm neurotechnology-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.

Cross region FMR at threshold T = 16.410 for algorithm vcog_001, giving FMR(T) = 0.001 globally.



Cross region FMR at threshold T = 0.095 for algorithm vigilantsolutions_000, giving FMR(T) = 0.001 globally.




Figure 15: For algorithm vigilantsolutions-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.

Cross country FMR at threshold T = 78.021 for algorithm dermalog_001, giving FMR(T) = 0.001 globally.




Figure 16: For algorithm dermalog-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give $\text{FMR} = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.

Cross country FMR at threshold T = 78.171 for algorithm dermalog_002, giving FMR(T) = 0.001 globally.




Figure 17: For algorithm dermalog-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give $\text{FMR} = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.


Cross country FMR at threshold $T = 0.091$ for algorithm ntechlab_000, giving $FMR(T) = 0.001$ globally.

Figure 18: For algorithm ntechlab-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.

Cross country FMR at threshold T = 2.869 for algorithm 3divi_000, giving $FMR(T) = 0.001$ globally.




Figure 19: For algorithm 3divi-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.

Cross country FMR at threshold T = 0.582 for algorithm rankone_000, giving FMR(T) = 0.001 globally.




Figure 20: For algorithm rankone-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.

Cross country FMR at threshold T = 30.260 for algorithm neurotechnology_000, giving FMR(T) = 0.001 globally.




Figure 21: For algorithm neurotechnology-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give $\text{FMR} = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.


Cross country FMR at threshold T = 16.410 for algorithm vcog_001, giving $\text{FMR}(T) = 0.001$ globally.

Figure 22: For algorithm vcog-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give $\text{FMR} = 0.001$ over all $O(10^{10})$ impostor comparisons. If text appears in each box it give the same quantity as that coded by the color. Light red colors present a security vulnerability to, for example, a passport gate.




Figure 23: For visa images, the heatmap shows The count of impostor comparisons of faces from different individuals who were born in the given country pair.

3.3.2 Effect of age on impostors

Background: This section shows the effect of age on the impostor distribution. The ideal behaviour is that the age of the enrollee and the impostor would not affect impostor scores. This would support FMR stability over sub-populations.

Goals:

- ▷ To show the effect of relative ages of the impostor and enrollee on false match rates.
- ▷ To determine whether some algorithms have better impostor distribution stability.

Methods:

- ▷ Define 14 age group bins, spanning 0 to over 100 years old.
- ▷ Compute FMR over all impostor comparisons for which the subjects in the enrollee and impostor images have ages in two bins.
- ▷ Compute FMR over all impostor comparisons for which the subjects are additionally of the same sex, and born in the same geographic region.

Results:

The notable aspects are:

- ▷ Diagonal dominance: Impostors are more likely to be matched against their same age group.
- ▷ Same sex impostors are more successful. On the diagonal, an impostor is more likely to succeed by posing as someone of the same sex. If $\Delta \log_{10} \text{FMR} = 0.2$, then same-sex FMR exceeds any-sex FMR by factor of $10^{0.2} = 1.6$. This is small relative to the age effect.
- ▷ Young children impostors give elevated FMR against young children. Older adult impostor give elevated FMR against older adults. These effects are quite large, for example if $\Delta \log_{10} \text{FMR} = 1.0$ larger than a 32 year old, then these groups have higher FMR by a factor of $10^1 = 10$. This would imply an FMR above 0.01 for a nominal (global) FMR = 0.001.
- ▷ Algorithms vary.
- ▷ We computed the same quantities for a global FMR = 0.0001. The effects are similar.

Note the calculations in this section include impostors paired across all countries of birth.

Cross age FMR at threshold T = 78.021 for algorithm dermalog_001, giving $FMR(T) = 0.001$ globally.




Figure 24: For algorithm dermalog-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. The text in each box it give the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.


Cross age FMR at threshold T = 78.171 for algorithm dermalog_002, giving $FMR(T) = 0.001$ globally.

Figure 25: For algorithm dermalog-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. The text in each box it give the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Cross age FMR at threshold $T = 0.091$ for algorithm ntechlab_000, giving $FMR(T) = 0.001$ globally.




Figure 26: For algorithm `ntechlab-000` operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. The text in each box it give the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.




Figure 27: For algorithm 3divi-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. The text in each box it give the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.


Cross age FMR at threshold T = 0.582 for algorithm rankone_000, giving $\text{FMR}(\text{T}) = 0.001$ globally.

Figure 28: For algorithm rankone-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give $\text{FMR} = 0.001$ over all $O(10^{10})$ impostor comparisons. The text in each box it give the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Cross age FMR at threshold $T = 30.260$ for algorithm neurotechnology_000, giving $\text{FMR}(T) = 0.001$ globally.




Figure 29: For algorithm neurotechnology-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give $\text{FMR} = 0.001$ over all $O(10^{10})$ impostor comparisons. The text in each box it give the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.


Cross age FMR at threshold $T = 16.410$ for algorithm vcog_001, giving $FMR(T) = 0.001$ globally.

Figure 30: For algorithm vcog_001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. The text in each box it give the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Cross age FMR at threshold $T = 0.095$ for algorithm `vigilantsolutions_000`, giving $FMR(T) = 0.001$ globally.




Figure 31: For algorithm `vigilantsolutions-000` operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give $FMR = 0.001$ over all $O(10^{10})$ impostor comparisons. The text in each box it give the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.